

AA G40 Automatic



G40 Automatic

G40 Automatic with manifold

Technical Specifications

| | |
|---|---|
| Maximum fluid pressure | 4000 psi (276 bar, 27.6 MPa) |
| Maximum working air pressure | 100 psi (7 bar, 0.7 MPa) |
| Max. cylinder air pressure | 100 psi (7 bar, 0.7 MPa) |
| Minimum actuating pressure | 50 psi (3.5 bar, 0.3 MPa) |
| Triggering speed | 60 msec (fully open or close) |
| Maximum working fluid temperature | 120°F (49°C) |
| Wetted parts | stainless steel, carbide, UHMWPE, acetal, polyethylene, chemically resistant fluorocelastomer, PTFE, polyimide |
| Gun weight | 1.2 lb (545 g) |
| Gun and manifold weight | 1.7 lb (770 g) |
| Air inlet | |
| Atomizing air | 3/8 in OD tube |
| Fan air | 3/8 in OD tube |
| Cylinder air | 1/4 in OD tube |
| Fluid inlet | 1/4 in npsm |
| Dimensions (excluding fittings) | 5.3 in L x 3.0 in H x 2.0 in W (135 mm L x 76 mm H x 51 mm W) |
| Instruction manual | 311052 |